

# Blastmate III™

## Full-Featured, Advanced Vibration and Overpressure Monitor

### Range of Applications:

- Blast-monitoring for compliance
- Near-field blast analysis
- Pile driving
- Construction activity
- Demolition activity
- Heavy transportation
- Bridge monitoring
- Structural analysis
- Underwater blast monitoring
- 4 or 8 channel data acquisition
- Remote monitoring - Auto Call Home™

Consultants, engineers and contractors the world over recognize the **Instantel® Blastmate III™** vibration and overpressure monitor as the most versatile and most reliable full featured monitor available. It provides all of the industry-leading features of the **Instantel Minimate Plus™** monitor, conveniently packaged with a full keyboard and a high-resolution printer. This allows you to setup, add notes and print complete event reports in the field, without a computer.

### Versatile

With standard features like the **Instantel Histogram Combo™** monitoring mode, zero dead-time between events, and flexible sample rates up to 65,536 S/s, the **Blastmate III** system provides you with control and confidence to monitor reliably in any situation. For added versatility, you have the option to add 4 more channels and extra memory, providing two complete standard monitors in a single package.

For more demanding monitoring applications, the **Instantel Blastware® Advanced Module** software provides the capability to monitor a broad selection of vibration and overpressure sensors, as well as sensors for related structural and environmental measurements. Monitor vibration, ambient environmental conditions, and the movement of structural cracks, all at the same time, all using the same **Blastmate III** monitor.

### Easy to use

The features and versatility of the **Blastmate III** monitor set it apart, but the fact that it is also easy to use makes it truly revolutionary. The dedicated single use function keys, backlit LCD and simple menu-driven operation make setup and operation quick and easy, even for inexperienced personnel.

### Tough

The **Blastmate III** monitor has been built to survive, with a fully sealed top panel, non-corrosive industrial grade connectors and sealed electronics, all packed in a rugged, water-resistant case.

**Blastmate III** - Reliability and versatility for any monitoring application.



### Key Features

- Fast high-resolution thermal printer for event reports in the field without the need for a computer.
- Full keyboard simplifies entry of job-specific notes and information.
- Dedicated function keys and intuitive menu-driven operation enable quick and easy setup.
- **Histogram Combo** mode allows capture of full waveform records while recording in histogram mode.
- Sample rates from 1,024 to 16,384 S/s per channel - up to 65,536 S/s available on a single channel.
- Available 8-channel option allows for 2 standard triaxial geophones and 2 microphones to be used on a single **Blastmate III** monitor.
- Continuous monitoring means zero dead time, even while the unit is processing.
- Any channel can be matched to a wide variety of sensors - geophones, accelerometers, or hydrophones.

# Blastmate III™

## General Specifications

## Blastmate III

Channels	Microphone and Triaxial Geophone or 4 independent user-configurable channels (two Microphones and two Triaxial Geophones or 8 independent channels with optional 8-channel upgrade)
Vibration Monitoring (with Standard Triaxial Geophone)	
Range	Up to 254 mm/s (10 in/s)
Resolution	0.127 mm/s (0.005 in/s) or 0.0159 mm/s (0.000625 in/s) with built-in preamp
Accuracy (ISEE / DIN)	+/- 5% or 0.5 mm/s (0.02 in/s), whichever is larger, between 4 and 125 Hz / DIN 45669-1 standard
Transducer Density	2.13 g/cc (133 lbs/ft <sup>3</sup> )
Frequency Range (ISEE / DIN)	2 to 250 Hz, within zero to -3 dB of an ideal flat response / 1 to 315 Hz
Maximum Cable Length (ISEE / DIN)	75 m (250 ft) / 1,000 m (3,280 ft)
Air Overpressure Monitoring	
Weighting Scales	Linear or A-weight
Linear Range	88 to 148 dB (500 Pa (0.072 PSI) Peak)
Linear Resolution	0.25 Pa (0.0000363 PSI)
Linear Accuracy	+/- 10% or +/- 1 dB, whichever is larger, between 4 and 125 Hz
Linear Frequency Response	2 to 250 Hz between -3 dB roll off points
A-weight Range	50 to 110 dBA
A-weight Resolution	0.1 dBA

## Waveform Recording

Record Modes	Manual, Single-shot, Continuous
Seismic Trigger	0.125 to 254 mm/s (0.005 to 10 in/s)
Acoustic Triggers	
Linear	100 to 148 dB
A-weight	55 to 110 dBA
Sample Rate	1,024 to 16,384 S/s per channel (independent of record time), up to 65,536 S/s in single-channel mode with advanced software (maximum 8,192 S/s per channel for 8 channels)
Record Stop Mode	Fixed record time, <b>Instantel® AutoRecord™</b> record stop mode
Record Time	1 to 100 seconds (programmable in one-second steps) or 500 seconds plus 0.25 seconds pre-trigger
<b>AutoRecord</b> Time	Auto window programmable from 1 to 9 seconds, plus a 0.25 second pre-trigger. Event is recorded until activity remains below trigger level for duration of auto window, or until available memory is filled. Recording uninterrupted by event processing - No dead time
Cycle Time	
Storage Capacity	
Full Waveform Events	300 one-second events at 1,024 S/s sample rate (1,500 event capacity with optional memory upgrade)
Event Summaries	1,750 (8,750 event capacity with optional memory upgrade)

## Histogram Recording

Record Modes	Histogram and <b>Instantel Histogram Combo™</b> (monitor captures triggered waveforms while recording in Histogram mode)
Recording Interval	2, 5 or 15 seconds; 1, 5 or 15 minutes
Storage Capacity	46,656 intervals - 3 days at 5-second intervals or 102 days at 15 minute intervals (with memory upgrade - 15 days at 5-second intervals or 540 days at 15 minute intervals)

## Physical Specifications

Dimensions	269 x 355 x 165 mm (10.6 x 14.0 x 6.5 in)
Weight	6.4 kg (14 lbs)
Battery	Rechargeable 6 V sealed gel cell - capacity for 30 days of continuous monitoring
User Interface	63 domed tactile keys including full keyboard and dedicated keys for common functions
Display	4-line x 20 character, high contrast, backlit LCD with online help
Printer	High resolution thermal plotter
PC Interface	RS-232
Auxillary Inputs and Outputs	External Trigger, Remote Alarm, coordinate download from GPS
Environmental	
Printer/LCD Operating Temperature	-10 to 50°C (14 to 122°F)
Electronics Operating Temperature	-20 to 60°C (-4 to 140°F)
Remote Communications	Compatible with Telephone, GSM, Cellular, RF, Satellite, Short-haul modems, and Ethernet® device servers. Automatically transfers events when they occur through <b>Instantel Auto Call Home™</b> feature.
Additional Features	Monitor start/stop timer

**Corporate Office:**  
309 Legget Drive,  
Ottawa, Ontario K2K 3A3  
Canada

**US Office:**  
808 Commerce Park Drive,  
Ogdensburg, New York 13669  
USA

Toll Free: (800) 267 9111  
Telephone: (613) 592 4642  
Facsimile: (613) 592 4296  
Email: sales@instantel.com



© 2009 Xmark Corporation. Instantel, the Instantel logo, Auto Call Home, AutoRecord, Blastmate, Blastware, Histogram Combo and Minimate, are trademarks of The Stanley Works or its affiliates.

